COOLSPLICE CONNECTORS

TE Connectivity's (TE) CoolSplice connectors elegantly combine reliability with ease of termination. The CoolSplice connector from TE is suitable for splicing 22 AWG to 18 AWG (0.34 mm²- 0.75 mm²) solid and stranded wire. A common pair of pliers is used to push-button terminate insulated wires into an insulation displacement crimp contact. An industry proven reliable connection is provided and visually confirmed through the clear sidewall of the CoolSplice connector.



Applications

- Commercial refrigeration lighting
- Display and cabinet lighting
- Lighting in furniture
- Outdoor lighting
- Signs and building façade lighting
- · Security and alarm systems
- · Audio speaker connections

Electrical

- Current / Voltage Rating:
- 18 AWG 5A Max at 450V AC/DC
- 20 AWG 5A Max at 450V AC/DC
- 22 AWG 3.5A Max at 450V AC/DC

Mechanical

- Ambient temperature between -40 C and 75 C
- CoolSplice operating temperature between -40 C and 105 C
- Suitable for 22 AWG to 18 AWG (0.34mm² 0.75mm²) solid and stranded (see product specifications)
- IP20, IPX5, IPX7 and IPX8 rating (2 hours, 1m under water)

Specifications

Product Specification: 108-133061
 Application Specification: 114-133061

Key Benefits

- Enable a waterproof solution with an IP rated splice
- · Suitable for solid and stranded wire
- · Time saving termination using standard tools
- · Fits through 16 mm hole

Product Compliance / Approvals

- IEC 60998-2-3
- UL 1977
- UL 2459 (pending)







Product Selection Information


	Description	Wire Size*	Sealed (Y/N)	Part Number
W. The	CoolSplice Connector	18 AWG 0.75 mm²	N	2213800-1
	CoolSplice Connector	18 AWG 0.75 mm²	Y	2213800-2
W. The	CoolSplice Connector	20-22 AWG 0.52 - 0.34 mm²	N	<u>2213800-3</u>
0	CoolSplice Connector	20-22 AWG 0.52 - 0.34 mm²	Y	2213800-4


^{*}Wire sizes corresponding to IEC60998-1

Dimensions









te.com

© 2016 TE Connectivity Ltd. Family of Companies. All Rights Reserved. CoolSplice, TE, TE Connectivity, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

1-1773884-7 JN 10/2016

USA: +1 (800) 522-6752 Canada: +1 (905) 475-6222 Mexico: +52 (0) 55-106-0800 Latin/S. America: +54 (0) 11-4733-2200 Germany: +49 (0) 6251-133-1999 UK: +44 (0) 800-267666 France: +33 (0) 1-3420-8686 The Netherlands: +31 (0) 73-6246-999 China: +86 (0) 400-820-6015

